## Canon

## LOFFLER

# QUALITY, QUANTITY, SPEED.

**Production Redefined** 



imagePROGRAF GP-6600S

imagePROGRAF GP-4600S

Cane

BRAND





imagePROGRAF GP-6600S

imagePROGRAF GP-4600S


The imagePROGRAF GP-4600S shown with optional multifunction roll unit.

The Canon imagePROGRAF 60" GP-6600S and 44" GP-4600S large-format printers, with the newly developed 7-Color LUCIA PRO II Ink System, are built to help bring production signage, advertisements, and businesses to the next level.



## **New LUCIA PRO II Ink Set**

- Excellent color accuracy
- · Large color gamut, particularly in dark areas
- Superb scratch resistance
- Excellent light-resistant pigment ink to help improve ink longevity
- Orange and Matte Black from the imagePROGRAF GP-4000/2000 helps enhance vivid eye-catching prints
- 96% of PANTONE<sup>™</sup> Formula Guide Solid and Coated\*



when using Premium Semi-Glossy Paper 2 with imagePROGRAF printer driver at [High] [Color Correction Off]













## **Features**

### **Designed to Achieve Robust Output**

Produces vivid color prints with more accurate color reproduction and improved black density color output than predecessor models.

- High scratch resistance
- High light resistance for longer term preservation of prints
- · Fast print speeds with L-COA PRO Processor



### **Color Calibration**

The ability to calibrate the printer for consistent color, this helps ensure the output is color consistent over time and across multiple imagePROGRAF GP S Series devices.

### Media Handling

- Intelligent media handling helps reduce time and waste
  - Automatic media feeding
  - Automatic media type, width, and length detection
  - Reduced media feed processing time from previous imagePROGRAF PRO S Series models
- Multifunction Roll Unit
  - Standard with the imagePROGRAF GP-6600S
  - Optional for the imagePROGRAF GP-4600S





imagePROGRAF GP-4600S

#### "Ease of Use" Body Design

- The user interface screen displays the ink levels, media indicator levels, and other setting prompts all on the home screen
- Easily see ink tanks and loaded media through translucent covers
- Interior LED light for reliable operation, such as previewing output while printing
- Hot-swap ink tanks

#### **Environmentally Conscious**

- EPEAT<sup>®</sup> Gold



- ENERGY STAR®

#### Software

**Professional Print and Layout** enables easy professional photo printing with editing and layout tools, as well as color management capabilities.

**Free Layout Plus** lets you nest, tile, and create custom layouts before printing your files with this print utility.

Accounting Manager helps track actual ink and media usage and costs.



The imagePROGRAF GP-4600S shown with optional multifunction roll unit.



## Printer Specs: imagePROGRAF GP-6600S/4600S

Print Head PF-10	Print Language Printer: SGRaster (Swift Graphic Raster), PDF, JPEG
Number of Nozzles 18,432 nozzles	Interface Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n) ■
Droplet Size Minimum 4 pl per color	Power Supply AC 100 - 240V (50 - 60 Hz)
Ink Type MBK, BK, C, M, Y, GY, O Ink Tank	Power Consumption Max: Approx. 94W Standby: Approx. 1.7W
Shipped with GP-4600S:           330ml Tank, Each Color MBK/BK/C/M/Y/GY/O           Shipped with GP-6600S:           330 ml Tank, Each Color MBK/BK/C/M/Y/GY/O           GP-4600S and GP-6600S Replacement:           160 ml PFI-3100 (BK, C, M, Y, GY), 160 ml PFI-2100 (MBK, O), 330 ml           PFI-3300 (BK, C, M, Y, GY), 330 ml PFI-2300 (MBK, O), 700 ml PFI-3700 (BK, C, M, Y, GY), 700 ml PFI-2700 (MBK, O)	Power Off: Approx. 0.1W Certifications ENERGY STAR® (Worldwide), EPEAT Gold
	Operational Environment Temperature: 59 – 86 °F (15 – 30 °C) Relative Humidity: 10 – 80% (Non Condensation)
Printer RAM Standard Memory: 3 GB Hard Disk: 500 GB	<ul> <li>Printer Dimensions (W x D x H) and Weight</li> <li>GP-4600S: (with stand and basket open) 62.7" x 38.7" x 46", 269 lbs</li> <li>GP-6600S: (with stand and basket open) 78.7" x 38.7" x 46", 373 lbs</li> </ul>
Media Feed GP-6600S: Front-Loading Roll Feed: Two* Rolls, Front Output GP-4600S: Front-Loading Roll Feed: One Roll, Front Output Cut Sheet: Upper-loading, Front Output (Manual feed using media locking lever)	Package Dimensions (W x D x H) and Weight GP-4600S: (main unit with pallet) 71.7" x 36" x 41", 399 lbs GP-6600S: (main unit with pallet) 87.7" x 36" x 40.4", 481 lbs Multifunction Roll Unit (physically strapped to printer) 84.0" x 22.1" x 18.1", 92.6 lbs
Media Width GP-4600S: Roll Feed: 6" - 44" (152.4 - 1,118 mm) Cut Sheet: 6" - 44" (152.4 - 1,118 mm) GP-6600S: Roll Feed: 6" - 60" (152.4 mm - 1,524 mm) Cut Sheet: 6" - 60" (152.4 mm - 1,524 mm)	Options           • Multifunction Roll Unit - PRO-2600 (RU-23) & PRO-4600 (RU-43)           • 2"/3" Roll Holder Set GP-4600S (RH2-46) & GP-6600S (RH2-66)           User Replaceable Items           • Ink Tank: PFI-3100/PFI-2100 (160ml), PFI-3300/PFI-2300 (330ml),
Media Cutter           Automatic horizontal cutting (Rotary cutter): standard	<ul> <li>PFI-3700/PFI-2700 (700ml)</li> <li>Print Head (PF-10)</li> <li>Maintenance Cartridge (MC-30)</li> </ul>
Media Thickness 0.002" - 0.03" (0.07 mm - 0.8 mm)	Cutter Blade (CT-07) What's In The Box
Media Core Sizes 2" Core Standard. 2"/3" Core Roll Holder Set GP-4600S (RH2-46) and GP-6600S (RH2-66)	<ul> <li>GP-4600S:</li> <li>Printer, 330 ml Starter Ink Tanks, 1 Print Head, Maintenance Cartridge (Installed),</li> <li>2" Roll Holder with 3" Adapters, Installation Guide, User Registration Card, One Year</li> <li>Printer Warranty Statement, Print Head Warranty Statement, Call Center Notice,</li> <li>Media Compatibility Flyer, PosterArtist Web Notice Flyer, Safety and Environmental</li> <li>Information, iWR Service Terms Leaflet, USB port (High Speed), Power Cable and</li> <li>Screw, Gigabit Ethernet (Built-in)</li> <li>GP-6600S:</li> <li>Printer, 330 ml Starter Ink Tanks, 1 Print Head, Maintenance Cartridge (Installed),</li> <li>Multifunction Roll Unit, 2" Roll Holder with 3" Adapters, Installation Guide, User</li> <li>Registration Card, One Year Printer Warranty Statement, Print Head Warranty</li> <li>Statement, Call Center Notice, Media Compatibility Flyer, PosterArtist Web Notice</li> <li>Flyer, Safety and Environmental Information, iWR Service Terms Leaflet, USB port</li> <li>(High Speed), Power Cable and Screw, Gigabit Ethernet (Built-in)</li> </ul>
Maximum Roll Outer Diameter 6.7" or less (170 mm or less)	
Media Output Catch Basket	
Printing Software Utilities Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist, Canon Print Service, Professional Print & Layout	
Operating System Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit), Macintosh OS v10.12.6 - v13x	







usa.canon.com/imagePROGRAF

#### To see all our branch locations, visit www.loffler.com/locations/

• Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients. \*If multifunction roll is used.

Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues.

Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Some security features may impact functionality/performance; you may want to test these settings in your environment.

Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. PANTONE® is a trademark or registered trademark of PANTONE® LLC. in the United States and/or other countries. As of January 26, 2024, according to professional services performed by PANTONE® under License Agreement between Canon, Inc. and PANTONE® LLC. PANTONE® Formula Guide Solid and Coated color gamut coverage rate is 96% for GP-6600S/GP-4600S when using Premium Semi-Glossy Paper with imagePROGRAF printer driver at (600 dpi). As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Wi-Fi is a registered trademark of the Wi-Fi alliance. All other referenced product names and marks are trademarks of their respective owners. All printer output and screen images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.