XEROX® PRIMELINK® PRINTER

The world's #1* entry production color printer just got even better.



C9065 AND C9070



Xerox[®] PrimeLink[®] C9065 and C9070 Printer

The Xerox[®] PrimeLink[®] C9065/C9070 delivers the most adaptable capabilities on the market. From superior image quality and unmatched media flexibility to professional-grade finishing, automation and security, it takes entry level to the next level.




IMPROVE YOUR IMAGE

Entry-level price point shouldn't mean entrylevel image quality. With PrimeLink, you can deliver stunning output on every job, every time.

It all starts with resolution. 2400 x 2400 dpi means you get outstanding fine-line detail and text with vivid images and smooth color transitions — even at speeds of up to 70 ppm. EFI servers with embedded PANTONE® technologies such as PANTONE® GOE and PANTONE® PLUS ensure the colors you want are the colors you get.

And a combination of Xerox® Emulsion Aggregation (EA) toner with ultra-low melt technology, +/- 1.5 mm front-to-back registration and Simple Image Quality Adjustment (SIQA) means you get consistent quality from your first print to your last.





WORK SMARTER, NOT HARDER

Looming deadlines are the norm. Now, there's no reason to compromise. Adding a PrimeLink to your arsenal lets you upgrade your productivity in ways you wouldn't think possible.

Designed to promote multitasking and collaboration, it's customizable to suit your work style. The Xerox[®] Integrated Color Server comes standard. Or you can choose from one of three optional EFI servers for more capabilities and more volume. All you have to do is select the best fit based on your business applications and the level of automation and color accuracy you need.

The printer also has access to the Xerox App Gallery. With apps that connect to leading applications including Box®, Microsoft® OneDrive®, Google Drive™, Dropbox™ and Microsoft Office 365™, you can print and scan directly to and from the cloud, simplify workflows and automate complex tasks.

Plus, built-in mobile connectivity with @PrintByXerox lets your team stay on-task when they're on the go. With this feature, PrimeLink can securely accept print submissions from any email-enabled device — no extra software required.

It's all there with the touch of a button. Say yes to more, and Xerox[®] PrimeLink C9065/C9070 will help you deliver.

SERVE AND PROTECT

PrimeLink applies a strategic approach to security to keep your network and projects safe from prying eyes. Stop suspicious activity where it starts with our comprehensive approach to security:

- Multiple layers of security include data encryption, access controls, disk overwrite and industry certifications.
- Audit Log ensures an audit trail of operators' key events. These logs are imperative for Administrators/Key Operators to use for troubleshooting, resource optimization and security audits.
- Secure Print holds documents for release until you're ready to retrieve them.
- Secure Scanning includes password protection for PDFs and folders, as well as encryption for scanning to email.

FINISH STRONG

PrimeLink delivers media latitude and finishing options that are best-in-class and unparalleled in an entry-level device.

Print on specialty stocks and heavyweight stocks up to 350 gsm. Print up to 26" (660 mm) with the Extra Long Sheet (XLS) capability up to 220 gsm. And print long runs without refilling the paper tray using high volume feeding options.

Finishing options are professional-grade, easy to navigate and nearly endless. Enjoy options ranging from full-bleed trimmed booklets to punch, crease and fold.




Xerox[®] PrimeLink[®] C9065/C9070 Printer

- **1 Two-Tray Oversized High Capacity Feeder:** Adds 4,000 sheets in sizes from 4 x 6 in. /100 x 148 mm to 13 x 19.2 in./330 x 488 mm (up to 350 gsm). Up to 13 x 26 in./330 x 660mm via Tray 5 (up to 220 gsm).
- 2 Extra Long Sheet (XLS) Capability: Print banners, book jackets, calendars and other applications up to 26 in. (660 mm) long, and up to 220 gsm via Tray 5 (Bypass).
- **3 Control Panel**: An intuitive user interface makes it simple to access general print, copy, scan and fax functions, integrated color server, useful apps from the Xerox App Gallery, color controls, security features and much more.
- **4 Integrated Scanner:** Single Pass Duplex Automatic Document Feeder scans up to 270 impressions per minute; 600 dots per inch color up to 11 x 17/A3. Scan to a variety of output options; desktop, USB, mailbox, FTP, SFTP, SMB and Job Flow multi-destination scanning.
- 5 Xerox[®] PrimeLink C9065/C9070 Printer: Prints, copies, scans and faxes all while delivering stunning color image quality at a highly productive 65 ppm color and 70 ppm black-and-white (C9065) or 70 ppm color and 75 ppm black-and-white (C9070).
- 6 Five Internal Trays (Standard): Includes a 12 x 18 in./SRA3 tray and Tray 5 (Bypass) max weight up to 350 gsm and up to 26 in./ 660 mm sheet size.
- 7 Xerox® Interface Decurler Module: Inline paper cooling and decurler unit improves throughput and efficiency, connecting Production Ready finishing modules, ensuring flat sheets for reliability and speed.

- **8 Xerox Inserter:** Insert preprinted or blank media into printed documents with a tray capacity of 250 sheets, sheet sizes up to 13 x 19.2 in. (330 x 488 mm) and 350 gsm.
- 9 GBC[®] AdvancedPunch Pro[™]: Lets you create bound documents in-house by combining printing, punching and collating into one convenient step. Choose the punch to fit your needs.
- **10 Xerox® Crease and Two-sided Trimmer:** Trims 6-25 mm from the head and foot of prints or booklets to produce an even edge and creases spine. Available with Production Ready Finishers.
- **11 Xerox® C/Z Folder:** Produces Z-fold, C-Fold and Engineering Z-Fold.
- 12 Xerox® Production Ready Finisher Booklet Maker: Ensures consistent high-quality stapled sets for small or large documents with a variable-length stapler, single or dual stapling option and a 100 sheet capacity. Plus, creates stapled booklets up to 30 sheets or 120 imposed pages (uncoated), or 15 sheets or 60 imposed pages (coated).
- **13 Xerox® SquareFold® Trimmer Module:** Enhances the power of the Production Ready Finisher with square fold of cover sheets and face trimming to produce booklets.

ADDITIONAL FEEDING AND FINISHING OPTIONS NOT PICTURED

- One-Tray Xerox® High Capacity Feeder Holds 2,000 sheets of 8.5 x 11 in. (A4) paper, 64–220 gsm.
- Banner Feed Guide An option for the Tray 5 (Bypass)/MSI/OHCF that increases reliability when feeding XLS or 350 gsm media.
- One-Tray Oversized High Capacity Feeder with Storage Cabinet — Adds 2,000 sheets in sizes from 4 x 6 in. / 100 x 148 mm to 13 x 19.2 in. / 330 x 488 mm (up to 350 gsm). Up to 13 x 26 in./330 x 660 mm via Tray 5 (up to 220 gsm).
- Offset Catch Tray 500-sheet stacking.
- Xerox[®] Business Ready Finisher A lighterduty option for finishing and stacking and staples up to 50 sheets uncoated/15 coated.
- Xerox[®] Business Ready Booklet Maker Finisher — Provides booklet making capability.
- Xerox[®] Production Ready Finisher Produces superior quality finishing and stacking with a 500-sheet top tray and 3,000-sheet stacker tray and built-in bi-directional decurler.
- Xerox[®] Production Ready Finisher Plus Provides same function as the Production Ready Finisher. Used to connect third-party inline finishing options.
- Xerox[®] Basic Punch An option for punching 2/3, 2/4 and Swedish 4-hole on the Production Ready Finisher and Booklet Maker.
- Plockmatic Pro 50/35 Booklet Maker Highest quality production booklets up to 200 pages (up to 50 sheets). Face trimming, square fold, rotate crease and bleed trim.
- Convenience Stapler Staples up to 50 sheets of 20 lb./80 gsm media.



Xerox[®] PrimeLink[®] C9065 and C9070 Printer

	PRIMELINK C9065	Direct, and white	PRIMELINK C9070	Direk and white
SIMPLEX SPEEDS		Black-and-white	Color	Black-and-white
8.5 x 11 in. / A4	Up to 65 ppm	Up to 70 ppm	Up to 70 ppm	Up to 75 ppm
I1 x 17 in. / A3	Up to 33 ppm	Up to 35 ppm	Up to 35 ppm	Up to 37 ppm
12 x 18 in. / SRA3	Up to 29 ppm	Up to 30 ppm	Up to 30 ppm	Up to 33 ppm
AUTO DUPLEX SPEEDS		Black-and-white	Color	Black-and-white
3.5 x 11 in. / A4	Up to 65 ppm 2-sided	Up to 70 ppm 2-sided	Up to 70 ppm 2-sided	Up to 75 ppm 2-sided
11 x 17 in. / A3	32 sheets per minute	35 sheets per minute	35 sheets per minute	37 sheets per minute
	Up to 32 ppm 2-sided 16 sheets per minute	Up to 35 ppm 2-sided 17 sheets per minute	Up to 35 ppm 2-sided 17 sheets per minute	Up to 37 ppm 2-sided
	Height: 54.8 in. / 1,391.5 mm; Width: 62 in. / 1,574 mm; Depth: 31 in. / 787 mm To sneets per minute To sneets per minute To sneets per minute To sneets per minute			18 sheets per minute
Printer Dimensions		•		
Monthly Duty Cycle	Up to 300,000 pages (maximum volume co	apacity expected in any one month, not exp	pected to be sustained on a regular basis)	
Average Monthly Print Volume (AMPV)	10,000 to 60,000 pages per month			
aper Flexibility/Weights	Standard Paper Capacity: 3,260 sheets (Tray 1 & 2: 500 sheets, Tray 3: 870 sheets, Tray 4: 1,140 sheets, Tray 5 (Bypass): 250 sheets) Max Paper Capacity: 7,260 sheets (Tray 1 & 2: 500 sheets, Tray 3: 870 sheets, Tray 4: 1,140 sheets, Oversized High Capacity Tray 1 & 2: 4,000 sheets) Sizes: Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to SRA3; Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3; Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4; Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4			
Image Quality Print Technology	Benchmark image quality with 2400 x 2400	dpi resolution with VCSEL ROS and EA Eco w	vith ultra-low melt technology toner for a smo	oth, offset-like finish
Line Screens	150/200/300/600 dot screen, 200 line scre	en. stochastic and enhanced text and arap	hics	
Registration	 Advanced registration technology for 			
Registration	Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (available on all configurations) +/- 1.5 mm. Variation will occur based on paper size, tray, etc.,			
Print Features	 Print, copy, fax and scan, including 	F	• XLS sheet size (Tray 5 and OHCF via	Fray 5) supporting up to 220asm
	Scan to PC, USB or Email, and mobile printing		 Up to 350 qsm (Tray 5 and OHCF only), 	
	Expansive media range lets you print everything from		auto-duplex up to 256 gsm (Bypass Tray and OHCF)	
	postcards to posters, both coated and uncoated stock, up to 350 gsm		Xerox® replaceable units for toners, drums, fuser, charge corotron, waste bottle, staples	
	 Xerox Extensible Interface Platform[®] (EIP) allows you to 			
	connect to third-party software solutions		• ·	
			Custom Paper Setup and Paper Catalog	
	Inline finishing options offer a professional polish with bapper printing stapling, hole-pupching, folding, and booklet		Load-while-run toner and paper capability	
	banner printing, stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters		Optional Features: Common Access Card Enablement	
	Kit, Accounting Options, Foreign Device Interface			
	Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted			
	Scan to Email, authentication and IPv	6 support		
Servers	Standard		Optional	
	Xerox® Integrated Color Server		 Xerox[®] EX-c C9065/C9070 Print Serve Xerox[®] EX-i C9065/C9070 Print Serve Xerox[®] EX C9065/C9070 Print Serve 	r Powered by Fiery®
Integrated Scanner	 Color or black-and-white scanner Scan to text searchable PDF, PDF/A, thumbnail preview, XPS[®], PCL[®] 6, HP-GL2 (direct submission), TIFF, JPEG 		• Up to 270 ipm (color, up to 200 gsm)	
			 Up to 270 ipm (black-and-white, up to 200 gsm) Originals up to 11 x 17 in. (A3) in weights from 38 gsm (16 lb. bond) to 200 gsm (53 lb. bond) 	
Optional Feeding	250-sheet capacity			
	Optional High Capacity Feeder (HCF): 2,000 sheets; 7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4);			
	16 lb. bond to 60 lb. cover / 64 to 220 gsm (uncoated and coated) Optional Oversized High Capacity Feeder (OHCF): One-Tray OHCF: 2,000 sheets plus Storage Cabinet; Tray 6: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in. / 330 x 488 mm (up to 350			
	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (up to 220 gsm).			
	gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (u	ip to 220 gsm).		
			/ 330 x 488 mm (up to 350 gsm) Tray 5: Up to 13	x 26 in./330 x 660 mm (up to 220 gsm).
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single: Other; 5.5 x 8.5 in. / A5 output to top tray; p	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstaplec -position staple) 8.5 x 11 in. / A4. Sizes: Stac bunch and offset. Paper weights: Top Tray-	/ 330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 d. Stacking Stapling Tray : 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (r	apled or 100 sets (dual or 4-position staple apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coated	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstaplec -position staple) 8.5 x 11 in. / A4. Sizes: Stac bunch and offset. Paper weights: Top Tray- d and uncoated).	d. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (c	apled or 100 sets (dual or 4-position stapl apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A oated and uncoated). Stacker Tray-16 lb.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coated	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstaplec -position staple) 8.5 x 11 in. / A4. Sizes: Stac bunch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8	d. Stacking Stapling Tray: 3,000 sheets uns cking: 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (8.5 x 11 in. / A4 unstapled. Stacking Stapling	apled or 100 sets (dual or 4-position stapl apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A oated and uncoated). Stacker Tray-16 lb.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 ib. cover / 60 to 256 gsm (coate: Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: Stac unch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A2	d. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (r 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or	apled or 100 sets (dual or 4-position stapl apling: 7.25 x 10.5 in. to 11 x 17 in. / B5 to A oated and uncoated). Stacker Tray-16 lb. Tray: 1 ,500 sheets unstapled or 200 sets
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single: Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate: Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. /	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: Stad ounch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 instaple) or 100 stapled sets of 11 x 17 in. / A2 (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. /	d. Stacking Stapling Tray: 3,000 sheets uns cking: 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (8.5 x 11 in. / A4 unstapled. Stacking Stapling	apled or 100 sets (dual or 4-position stapl apling: 7.25 x 10.5 in. to 11 x 17 in. / B5 to A oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single: Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; pu	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: Stad punch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is staple) or 100 stapled sets of 11 x 17 in. / A2 (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16	d. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (r 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 'A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17	apled or 100 sets (dual or 4-position stapl apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated),
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-positior 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 tr	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: 5tat position staple) 8.5 x 11 in. / A4. sizes: 5tat ouch and offset. Paper weights: Top Tray-' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A' (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in./ unch and offset. Paper weights: Top Tray-16 o 256 gsm (coated and uncoated). Booklet M	d. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (i 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 5 lb. bond to 130 lb. cover / 60 to 350 gsm (coo	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to <i>J</i> oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in./ Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 to (uncoated, 106 to 220 gsm (coated)). Booklet	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: State bounch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A3 A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in./ anch and offset. Paper weights: Top Tray- 10 z56 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 sheet	d. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (r 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 5 lb. bond to 130 lb. cover / 60 to 350 gsm (coa vlaker-16 lb. bond to 96 lb. cover / 60 to 256 gs	apled or 100 sets (dual or 4-position stap apling: 7.25 x 10.5 in. to 11 x 17 in. / B5 to / oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated).
Dptional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single: Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate: Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-positior 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 to (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: Stac unch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 instaple) or 100 stapled sets of 11 x 17 in. / A3 'A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-for 0 256 gsm (coated and uncoated). Booklet 6 t Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 'eight: 350 gsm. Options: Punch, Inserter an	d. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (r 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 i lb. bond to 130 lb. cover / 60 to 350 gsm (co adker-16 lb. bond to 96 lb. cover / 60 to 256 gs ets at 106 to 176 gsm coated or 5 sheets at 17	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to , oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x
Dptional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-positior 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 tr (uncoated, 106 to 220 gsm (coated)). Booklet Production Ready Finisher (requires Inte 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: 5ta position staple) 8.5 x 11 in. / A4. Sizes: 5ta ouch and offset. Paper weights: Top Tray-' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A' (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in./ unch and offset. Paper weights: Top Tray-'f6 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 eight: 350 gsm. Options: Punch, Inserter an mm.	A. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (o 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 46 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 5 lb. bond to 130 lb. cover / 60 to 350 gsm (co daker-16 lb. bond to 96 lb. cover / 60 to 256 gs ets at 106 to 176 gsm coated or 5 sheets at 17 9 sheets (90 gsm) uncoated, 35 sheets (90 gs dd C/Z Folder. Trays: Two output trays, 500-sh	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x eet top tray, 3,000-sheet stack tray of 5.8
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-positior 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2''/330 x 488 Production Ready Finisher Plus (requires	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: 5tar position staple) 8.5 x 11 in. / A4. sizes: 5tar bunch and offset. Paper weights: Top Tray. ⁻ d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is staple) or 100 stapled sets of 11 x 17 in. / A ² (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in./ unch and offset. Paper weights: Top Tray-16 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 'eight: 350 gsm. Options: Punch, Inserter an mm. : Interface Decurler Module): Provides sar	d. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (r 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 ib. bond to 130 lb. cover / 60 to 350 gsm (co adker-16 lb. bond to 96 lb. cover / 60 to 256 gs ets at 106 to 176 gsm coated or 5 sheets (90 gs id C/Z Folder. Trays: Two output trays, 500-sl me function as the Production Ready Finishe	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x eet top tray, 3,000-sheet stack tray of 5.8
Dptional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 to (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2''330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: State bounch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is staple) or 100 stapled sets of 11 x 17 in. / A3 :A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / anch and offset. Paper weights: Top Tray-16 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 reight: 350 gsm. Options: Punch, Inserter an mm. : Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne	J. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (c 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 is lb. bond to 130 lb. cover / 60 to 350 gsm (co advaer-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets (90 gsm) uncoated, 35 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dr // Z lolder. Trays: Two output trays, 500-sheet function as the Production Ready Finisher Finishing Interface Module.	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x ieet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she
Dptional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coated Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-positior 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 to (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: Stac bunch and offset. Paper weights: Top Tray.' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A3 'A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray.' anch and offset. Paper weights: Top Tray.' and and offset. Paper weights: Top Tray.' in the different of the state of	d. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (r 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 'A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 5 lb. bond to 130 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co a/aker-16 lb. bond to 176 gsm co ated or 5 sheets (90 gsm) unco ated, 35 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 sheets (so gsm (co a/aker-16 gsm co ated o/ 5 s	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated), m) coated. Paper Size: 7.2 x 5.7"/182 x eet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she o 13 x 19.2"/330 x 488mm up to 256 gsm.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 ar Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coate: Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-positior 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; pu Stacker Tray-16 lb. bond to 96 lb. cover / 60 tr (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2'/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party inl Production Ready Finisher with Booklet L Trays: 500-sheet top tray, 2,000-sheet stac	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: Stac bunch and offset. Paper weights: Top Tray.' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A3 'A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray.' anch and offset. Paper weights: Top Tray.' and and offset. Paper weights: Top Tray.' in the different of the state of	J. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (c 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 is lb. bond to 130 lb. cover / 60 to 350 gsm (co advaer-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets (90 gsm) uncoated, 35 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dr // Z lolder. Trays: Two output trays, 500-sheet function as the Production Ready Finisher Finishing Interface Module.	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x eet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she o 13 x 19.2"/330 x 488mm up to 256 gsm.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 446mm to 11.7 x 17'/297 x 432mm. Max W 5.75'/148 x 146mm to 13 x 19.2'/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party ini Production Ready Finisher with Booklet Trays: 500-sheet top tray, 2,000-sheet stack Offset Catch Tray: 500-sheet stacking.	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: 5tar position staple) 8.5 x 11 in. / A4. Sizes: 5tar bunch and offset. Paper weights: Top Tray-' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A' (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-'6 to 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee rface Decurler Module): Booklet Size: 100 leight: 350 gsm. Options: Punch, Inserter an mm. E Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module) tray k tray, saddle-stitch booklet tray (up to 120	J. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (id 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 'A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 5 lb. bond to 130 lb. cover / 60 to 350 gsm (cod vlaker-16 lb. bond to 96 lb. cover / 60 to 256 gst sta to 106 to 176 gsm coated or 5 sheets at 17 9 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dr C/Z Folder. Trays: Two output trays, 500-sheet Finishing Interface Module.	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x eet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she o 13 x 19.2"/330 x 488mm up to 256 gsm. ts/106 gsm coated).
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in./ Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 tr (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet 1 Trays: 500-sheet top tray, 2,000-sheet stacking. Xerox® SquareFold® Trimmer Module: For	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. Sizes: 5tac position staple) 8.5 x 11 in. / A4. Sizes: 5tac bunch and offset. Paper weights: Top Tray. ⁻ d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A: (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 leight: 350 gsm. Options: Punch, Inserter an mm. Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): tray. Maker (requires Interface Decurler Module): tray. Interface The Sitch 2 to 120 Maker (requires Interface Decurler Module): tray. Maker	J. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (id. 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 ilb. bond to 130 lb. cover / 60 to 350 gsm (co. 40ker-16 lb. bond to 96 lb. cover / 60 to 256 gsets at 106 to 176 gsm coated or 5 sheets (90 gsm) uncoated, 35 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dC/Z Folder. Trays: Two output trays, 500-sfm function as the Production Ready Finisher Finishing Interface Module.	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to , oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x seet top tray, 3,000-sheet stack tray of 5.8 rwith a 500-sheet top tray and 2,000-she o 13 x 19.2"/330 x 488mm up to 256 gsm. ts/106 gsm coated). r, Crease and Two-Sided Trimmer.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 to (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet I Trays: 500-sheet top tray, 2,00-sheet stacking. Xerox® SquareFold® Trimmer Module: Fa Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (A4	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. Sizes: 5tac position staple) 8.5 x 11 in. / A4. Sizes: 5tac bunch and offset. Paper weights: Top Tray. ⁻ d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A: (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 leight: 350 gsm. Options: Punch, Inserter an mm. Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): tray. Maker (requires Interface Decurler Module): tray. Interface The Sitch 2 to 120 Maker (requires Interface Decurler Module): tray. Maker	J. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (id 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 'A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 5 lb. bond to 130 lb. cover / 60 to 350 gsm (cod vlaker-16 lb. bond to 96 lb. cover / 60 to 256 gst sta to 106 to 176 gsm coated or 5 sheets at 17 9 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dr C/Z Folder. Trays: Two output trays, 500-sheet Finishing Interface Module.	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x seet top tray, 3,000-sheet stack tray of 5.8 rwith a 500-sheet top tray and 2,000-she o 13 x 19.2"/330 x 488mm up to 256 gsm. ts/106 gsm coated). r, Crease and Two-Sided Trimmer.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-positior 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 to (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/300 x 48 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet Trays: 500-sheet top tray, 2,000-sheet stacking. Xerox® SquareFold® Trimmer Module: Foa Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (Af Finisher, Booklet Maker.	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: Stac bunch and offset. Paper weights: Top Tray.' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 in staple) or 100 stapled sets of 11 x 17 in. / A3 'A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / anch and offset. Paper weights: Top Tray.' anch and offset. Paper weights: Top Tray.' Booklet N at Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 leight: 350 gsm. Options: Punch, Inserter an mm. Einerfinshing options. Includes PFIM Partne Maker (requires Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module): Compatibili 4). Half-Z Fold Sheet Size: Larger stocks redu	J. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (d 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 'A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 ilb. bond to 130 lb. cover / 60 to 350 gsm (co 4/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co 4/aker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co 4/aker-16 lb. bond to 97 bord to 350 gsm (co 5/aker-17 cover) and the start of the st	apled or 100 sets (dual or 4-position stag apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7'/182 x leet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she o 13 x 19.2'/330 x 488mm up to 256 gsm. ts/106 gsm coated). r, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookk Production Ready Finisher (requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75''/148 x 146mm to 13 x 19.2''/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party ini Production Ready Finisher with Booklet 1 Trays: 500-sheet top tray; 2,000-sheet stac Offset Catch Tray: 500-sheet stacking. Xerox® C/Z Folder: Sheet Size: 8.5 x 11' (AF Finisher, Booklet Maker.	ad 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: 5ta position staple) 8.5 x 11 in. / A4. Sizes: 5ta ouch and offset. Paper weights: Top Tray-' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A' (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in./ unch and offset. Paper weights: Top Tray-'6 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 leight: 350 gsm. Options: Punch, Inserter an mm. Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module) tk tray, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili 4). Half-ZFold Sheet Size: Larger stocks redu pabilities: Trimming, punching, folding, stag	J. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (id. 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 ilb. bond to 130 lb. cover / 60 to 350 gsm (co. 40ker-16 lb. bond to 96 lb. cover / 60 to 256 gsets at 106 to 176 gsm coated or 5 sheets (90 gsm) uncoated, 35 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dC/Z Folder. Trays: Two output trays, 500-sfm function as the Production Ready Finisher Finishing Interface Module.	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7'/182 x leet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she o 13 x 19.2'/330 x 488mm up to 256 gsm. ts/106 gsm coated). r, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party ini Production Ready Finisher with Booklet I Trays: 500-sheet top tray, 2,000-sheet stac Offset Catch Tray: 500-sheet stacking. Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (Af Finisher, Booklet Maker.	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. Sizes: 5tar position staple) 8.5 x 11 in. / A4. Sizes: 5tar bunch and offset. Paper weights: Top Tray.' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A2 (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray-16 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 leight: 350 gsm. Options: Punch, Inserter an mm. E Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module) t ray, saddle-stitch booklet tray (up to 120 uce Trim: 120 pages (30 sheets). Compatibili 4). Half-Z Fold Sheet Size: Larger stocks redu pabilities: Trimming, punching, folding, stap n Ready Finisher.	J. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (compared of the start of the st	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size; 7.2 x 5.7"/182 x seet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she o 13 x 19.2"/330 x 488mm up to 256 gsm. ts/106 gsm coated). r, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready 8 mm) to 13 x 19.2" (330 x 488 mm). Max
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in./ Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 to (uncoated, 106 to 220 gsm (coated)). Bookle Production Ready Finisher (requires Inte 146mm to 11.7 x 17"/297 x 432mm. Max W 5.75"/148 x 146mm to 13 x 19.2"/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party in Production Ready Finisher with Booklet 1 Trays: 500-sheet top tray, 2,000-sheet stacking. Xerox® GyaareFold® Trimmer Module: Fa Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (AF Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. Cap Weight: 350 gsm. Compatibility: Production Xerox® Crease/Two-sided Trimmer: Trim	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. Sizes: Star position staple) 8.5 x 11 in. / A4. Sizes: Star bunch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A3 'A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray- 10 staple) or 100 stapled sets of 11 x 17 in. / A3 'A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / unch and offset. Paper weights: Top Tray- 16 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 leight: 350 gsm. Options: Punch, Inserter an mm. Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module) t tray, saddle-stitch booklet tray (up to 120 uce Trim: 120 pages (30 sheets). Compatibili 4). Half-Z Fold Sheet Size: Larger stocks redu pabilities: Trimming, punching, folding, star n Ready Finisher. Range: 0.236' (6 mm) to 0.985'' (25 mm). Po	d. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (c 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or /A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 ib. bond to 130 lb. cover / 60 to 350 gsm (co advaer-16 lb. bond to 96 lb. cover / 60 to 256 gs ts at 106 to 176 gsm coated or 5 sheets at 17) sheets (90 gsm) uncoated, 35 sheets (90 gs id C/Z Folder. Trays: Two output trays, 500-sf me function as the Production Ready Finishe er Finishing Interface Module. ule): Booklet Size: 7.17 x 7.17'/182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 shee ity: Production Ready Finisher, Booklet Make ucing to 8.5 x 11" (A4). Weight Range: 64 - 90 pling, stacking. Paper Size: 7.2 x 5.8" (182 x 14 aper Size: 7.7 x 8.3"/194 x 210 mm to 13 x 19.	apled or 100 sets (dual or 4-position stap apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7"/182 x leet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she o 13 x 19.2"/330 x 488mm up to 256 gsm. ts/106 gsm coated). r, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready 8 mm) to 13 x 19.2" (330 x 488 mm). Max 2"/330 x 488 mm.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 to (uncoated, 106 to 220 gsm (coated)). Booklet Production Ready Finisher (requires Inter 146mm to 11.7 x 177/297 x 432mm. Max W 5.75°/148 x 146mm to 13 x 19.2°/330 x 488 Production Ready Finisher Pitel (requires stacker tray. Used to connect third-party inl Production Ready Finisher with Booklet I Trays: 500-sheet top tray, 2,000-sheet stacd Offset Catch Tray: So0-sheet stacking. Xerox® SquareFold® Trimmer Module: Fa Xerox® Inserter: Capacity: 250 sheets, Cap Weight: 350 gsm. Compatibility: Production Max Weight: 350 gsm. Compatibility: Production Max Weight: 350 gsm. Compatibility: Production Hor Market I and Partice	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2in./ Tray: 500-sheets 8.5 x 11 in. / A4 unstapled -position staple) 8.5 x 11 in. / A4. Sizes: Stac bunch and offset. Paper weights: Top Tray- d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A3 'A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / anch and offset. Paper weights: Top Tray-16 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee erface Decurler Module): Booklet Size: 100 eight: 350 gsm. Options: Punch, Inserter an mm. S Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module) tay, saddle-stitch booklet tray (up to 120 ace Trim: 120 pages (30 sheets). Compatibili 4). Half-Z Fold Sheet Size: Larger stocks redu pabilities: Trimming, punching, folding, stap n Ready Finisher. Range: 0.236' (6 mm) to 0.985'' (25 mm). Po Jaction Ready Finisher and Booklet Maker. Ba	J. Stacking Stapling Tray: 3,000 sheets unscking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (compared of the start of the st	apled or 100 sets (dual or 4-position stag apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7*/182 x leet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she o 13 x 19.2*/330 x 488mm up to 256 gsm. ts/106 gsm coated). r, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready 8 mm) to 13 x 19.2* (330 x 488 mm). Max 2*/330 x 488 mm. ain or valley creases per sheet.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 to (uncoated, 106 to 220 gsm (coated)). Booklet Production Ready Finisher (requires Inter 146mm to 11.7 x 177/297 x 432mm. Max W 5.75°/148 x 146mm to 13 x 19.2°/330 x 488 Production Ready Finisher Pitel (requires stacker tray. Used to connect third-party inl Production Ready Finisher with Booklet I Trays: 500-sheet top tray, 2,000-sheet stacd Offset Catch Tray: So0-sheet stacking. Xerox® SquareFold® Trimmer Module: Fa Xerox® Inserter: Capacity: 250 sheets, Cap Weight: 350 gsm. Compatibility: Production Max Weight: 350 gsm. Compatibility: Production Max Weight: 350 gsm. Compatibility: Production Hor Market I and Partice	nd 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: 5ta position staple) 8.5 x 11 in. / A4. Sizes: 5ta ouch and offset. Paper weights: Top Tray-' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A' (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in./ unch and offset. Paper weights: Top Tray-'6 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee brace Decurler Module): Booklet Size: 100 oright: 350 gsm. Options: Punch, Inserter an mm. Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module) t tray, saddle-stitch booklet tray (up to 120 aree Trim: 120 pages (30 sheets). Compatibili 4). Half-ZFold Sheet Size: Larger stocks redu pabilities: Trimming, punching, folding, stagn n Ready Finisher. Range: 0.236' (6 mm) to 0.985'' (25 mm). Pc uction Ready Finisher and Booklet Maker. Bi oklet Capacity: 200 pages (50 sheets). Caper oklet Capacity:	A. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (o 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 'A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 3 lb. bond to 130 lb. cover / 60 to 350 gsm (co vlaker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co vlaker-16 lb. bond to 96 lb. cover / 60 to 256 gs sta 106 to 176 gsm coated or 5 sheets at 17 0 sheets (90 gsm) uncoated, 35 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sł me function as the Production Ready Finishe r Finishing Interface Module. ule): Booklet Size: 7.17 x 7.17"/182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 shee ity: Production Ready Finisher, Booklet Make ucing to 8.5 x 11" (A4). Weight Range: 64 - 90 pling, stacking. Paper Size: 7.2 x 5.8" (182 x 14 aper Size: 7.7 x 8.3"/194 x 210 mm to 13 x 19. uffering Unit: Up to five customizable mount abilities: Face trimming, square fold, rotate c	apled or 100 sets (dual or 4-position stag apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated), m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7*/182 x leet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she o 13 x 19.2*/330 x 488mm up to 256 gsm. ts/106 gsm coated). r, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready 8 mm) to 13 x 19.2* (330 x 488 mm). Max 2*/330 x 488 mm. ain or valley creases per sheet.
Optional Finishing	Two-Tray OHCF: 4,000 sheets; OHCF: Tray 6 an Business Ready Finisher: Offsetting Top 11x17 in., 8.5 x 14 in., A3 or 200 sets (single Other; 5.5 x 8.5 in. / A5 output to top tray; p bond to 96 lb. cover / 60 to 256 gsm (coater Business Ready Finisher Booklet Maker F (single position stapling or dual or 4-position 200 sets (single-position staple) 8.5 x 11 in. / Other; 5.5 x 8.5 in. / A5 output to top tray; p Stacker Tray-16 lb. bond to 96 lb. cover / 60 t (uncoated, 106 to 220 gsm (coated)). Bookk Production Ready Finisher Requires Inte 146mm to 11.7 x 17'/297 x 432mm. Max W 5.75''/148 x 146mm to 13 x 19.2''/330 x 488 Production Ready Finisher Plus (requires stacker tray. Used to connect third-party ini Production Ready Finisher vith Booklet 1 Trays: 500-sheet top tray; 2,000-sheet stac Offset Catch Tray: 500-sheet stacking. Xerox® C/Z Folder: Sheet Size: 8.5 x 11'' (AF Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. Cap Weight: 350 gsm. Compatibility: Production Xerox® Craese/Two-sided Trimmer: Trim Max Weight: 350 gsm. Compatibility: Production Plockmatic Pro 50/35 Booklet Maker: Boo Paper Size: Up to 12.6 x 9'' (320 x 228.6 mm	ad 7: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ Tray: 500-sheets 8.5 x 11 in. / A4. sizes: 5tar position staple) 8.5 x 11 in. / A4. Sizes: 5tar ouch and offset. Paper weights: Top Tray-' d and uncoated). Finisher: Offsetting Top Tray: 500-sheets 8 is taple) or 100 stapled sets of 11 x 17 in. / A' (A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in./ unch and offset. Paper weights: Top Tray-'6 o 256 gsm (coated and uncoated). Booklet N et Maker-Saddle-stitch 2 to 16 sheets (7 shee rface Decurler Module): Booklet Size: 100 (eight: 350 gsm. Options: Punch, Inserter an mm. Interface Decurler Module): Provides sar line finishing options. Includes PFIM Partne Maker (requires Interface Decurler Module) t tray, saddle-stitch booklet tray (up to 120 cc Trim: 120 pages (30 sheets). Compatibili 4). Half-Z Fold Sheet Size: Larger stocks redu pabilities: Trimming, punching, folding, stag n Ready Finisher. Range: 0.236' (6 mm) to 0.985'' (25 mm). Pc uction Ready Finisher and Booklet Maker. Bid oklet Capacity: 200 pages (50 sheets). Capatibility). Max Weight: 300 gsm. Compatibility: Pro	A. Stacking Stapling Tray: 3,000 sheets uns cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, St 16 lb. bond to 130 lb. cover / 60 to 350 gsm (o 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 'A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 17 3 lb. bond to 130 lb. cover / 60 to 350 gsm (co vlaker-16 lb. bond to 96 lb. cover / 60 to 350 gsm (co vlaker-16 lb. bond to 96 lb. cover / 60 to 256 gs sta 106 to 176 gsm coated or 5 sheets at 17 0 sheets (90 gsm) uncoated, 35 sheets (90 gs d C/Z Folder. Trays: Two output trays, 500-sł me function as the Production Ready Finishe r Finishing Interface Module. ule): Booklet Size: 7.17 x 7.17"/182 x 182mm t pages, 30 sheets/90 gsm uncoated, 15 shee ity: Production Ready Finisher, Booklet Make ucing to 8.5 x 11" (A4). Weight Range: 64 - 90 pling, stacking. Paper Size: 7.2 x 5.8" (182 x 14 aper Size: 7.7 x 8.3"/194 x 210 mm to 13 x 19. uffering Unit: Up to five customizable mount abilities: Face trimming, square fold, rotate c	rapled or 100 sets (dual or 4-position stag apling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to oated and uncoated). Stacker Tray-16 lb. Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. ted and uncoated). m 7 to 220 gsm coated). m) coated. Paper Size: 7.2 x 5.7'/182 x seet top tray, 3,000-sheet stack tray of 5.8 r with a 500-sheet top tray and 2,000-she to 13 x 19.2''/330 x 488mm up to 256 gsm ts/106 gsm coated). r, Crease and Two-Sided Trimmer. gsm. Compatibility: Production Ready 8 mm) to 13 x 19.2'' (330 x 488 mm). Max 2''/330 x 488 mm. ain or valley creases per sheet. rease and bleed trim.

Configurations vary by geographical location.

For more information, go to **xerox.com/PrimeLink**.

©2020 Xerox Corporation. All rights reserved. Xerox®, PrimeLink®, Smart Kit®, SquareFold® and Xerox Extensible Interface Platform® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 02/20 PN03829 BR26905 PC9BR-01UC

